



## SELF-REGULATING TIDAL GATES

AWMA's Self-Regulating Tidal Gate operates via floatation to autonomously manage storm, flood and/or tidal water intrusion.

### FEATURES

- Typically used to prevent upstream saline intrusion in storm water retention basins.
- Self-regulating, according to a pre-determined head differential.
- A 25 year design life in demanding conditions.
- The gate is centrally hinged and operates via floatation for automatic positioning, enabling optimal stormwater retention or flow requirements.
- Instantaneous response time.
- Guaranteed failsafe opening.
- Functions autonomously without operator intervention.

### APPLICATIONS

- Wetland entry/exit points
- Storm Water Harvesting
- Tidal Water Intrusion Zones
- Flood Water Diversions



# SELF-REGULATING TIDAL GATES



## DESIGN

### DESIGN SUPPORT

- AWMA's design team will provide full support to ensure the most appropriate solution is developed and specified during the preliminary design.

### SIZES

- All AWMA Systems are custom sized to ensure they meet specific site requirements.

### MATERIALS

- AWMA select materials to meet a minimum design life of 25 years. Where required, AWMA can offer higher grade materials, coatings and protection systems to extend the design life to 100+ years.
- Gates and frames are manufactured from marine grade aluminium.
- AWMA use ultra high molecular weight polyethylene (UHMWPE) for barrier guides to provide maintenance free bearing surfaces.
- Plasticised PVC or EPDM are used for the manufacture of seals.
- Materials used have a high corrosion resistance and can be operated for many years with minimal maintenance.

### SEALING

- The seal performance exceeds that required by the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.

### MAINTENANCE

- The Gate has a minimum 25 year design life.
- Minimal maintenance is required ensuring low 'whole of life costs'.

## MANUFACTURE

### QUALITY

- All fabrication is in accordance with the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.
- All procedures are in accordance with AWMA's accredited ISO 9001 Quality Management System to ensure each gate is manufactured to a high standard, tested and ready for trouble free operation post approved installation.

## INSTALLATION

### MOUNTING OPTIONS

- AWMA Tidal Gates are designed to retrofit existing infrastructure or 'green field sites'.
- AWMA offer install supervision for all turn-key installations.

### ACTUATION SYSTEMS

- Not applicable. The AWMA Self-regulating Tidal Gate is designed to operate automatically.

### OPERATION SYSTEMS

- Not required. The AWMA Self-regulating Tidal Gate is designed to operate automatically, without operator intervention, for instantaneous protection.

## COMMISSIONING

### DOCUMENTATION AND TRAINING

- Detailed documentation on operation, testing procedures and maintenance is available for all AWMA systems.
- Comprehensive on and/or off site training available.



### HEAD OFFICE

Phone +61 3 5456 3331 Email [info@awmawatercontrol.com.au](mailto:info@awmawatercontrol.com.au)  
118 Roviras Road, PO Box 433, Cohuna Victoria 3568, Australia.

[www.awmawatercontrol.com.au](http://www.awmawatercontrol.com.au)