

# i-RISER™ IRRIGATION RISERS

## INNOVATIVE RELIABLE RISERS

### FEATURES OF THE i-RISER

Easy to open and close via crank handle or battery drill.

Standard units fit ø355mm and ø315mm pipe.

Zero leakage for the life of the riser.

Tested to 20m head pressure.

The hydrodynamic seal allows the riser to be operated with very low force.

Marine grade aluminium construction.

Easily retrofitted to any new or existing Pipe and Riser Systems.

Low torque operation. No straining to break the seal when opening, or to make the seal when closing.

Fully integrated structure for maximum effectiveness and mechanical protection.

The design creates a rear shroud minimising backwash and protecting the operator from getting wet when operating manually.

Livestock friendly, reducing the possibilities of damage to all components of the i-Riser.

Non-rising spindle (spindle does not protrude from the top of the i-Riser when open). NEW low maintenance spindle nut.

Also available in ø450mm which has been pressure tested to 10m.

### FEATURES OF THE i-RISER PLUS

Mitigate potential pipeline failure and increase pumping efficiency.

Internal Vacuum Relief System.

Internal Air Release Valve.



Phone 1800 664 852

Email [info@awmawatercontrol.com.au](mailto:info@awmawatercontrol.com.au)

[www.iriser.com.au](http://www.iriser.com.au)

**awma**  
Water Control Solutions